

Connectivity with No Boundaries



With the ultra-portable, flat-panel ThinPack antenna, users in the field can stream video, make calls and take high-speed satcom anywhere cellular networks don't exist or aren't viable.

Key Features

- Worldwide satellite coverage (Ku, Ka and X bands)
- Compatible with wide-beam and HTS services
- Network and modem agnostic
- Up to 20 Mbps down x 10 Mbps up
- No assembly required
- Fast and easy to align and stabilize
- Lightweight and compact, easily transported
- Airline carry-on case available (IATA compliant)
- Panel-only options readily adaptable to all integrators' terminal solutions



TECHNICAL SPECIFICATIONS

Performance Advantages

Fueled by patented technology, ThinPacks outperform parabolic dishes and other flat-panel antennas on many fronts:

- High spectral efficiency
- Broad channel bandwidth
- Low OpEx
- High performance in rain/wind
- Low prime power
- Convenient portability



Integration options and technical enhancements, beyond the standard configurations below, are available upon request.

Specification	Ku100	Ku100i	Ka100	X100
Frequency Band	Ku-band		Ka-band	X-band
Transmit (Tx) Band	13.75-14.5 GHz		28.1-31.0 GHz	7.90 to 8.40 GHz
Receive (Rx) Band	10.7-12.75 GHz		18.7-21.2 GHz	7.25 to 7.75 GHz
G/T	9.0 dB/K (12.25 GHz)	11.5 dB/K (12.25 GHz)	13 dB/K (20.2 GHz)	6.5 dB/K (7.5 GHz)
EIRP	39.5 dBW (14.25 GHz w/6 W BUC)*	40 dBW (14.25 GHz w/6 W BUC)*	46 dBW (30 GHz w/5 W BUC)*	37.5 dBW (8.15 GHz w/10 W BUC)*
Transmit PSD (Regulatory Compliance)	12.5 dBW/4 kHz (per 47 CFR 25.222, 25.209)	15 dBW/4 kHz H-Pol (per 47 CFR 25.222, 25.209)	32 dBW/40 kHz (per 47 CFR 25.138)	12 dBW/4 kHz (per MIL-STD-188-164A)
Parabolic Dish Equivalent	40-45 cm	45-50 cm	60-65 cm	40-45 cm
Polarization	Linear (manually aligned)		Switchable circular	Switchable circular
X-Pol/AR	<20 dB typical (X-pol)		<2.0 dB typical (AR)	<2.0 dB typical (AR)
Tx/Rx Isolation	<-80 dB (built-in diplexer/filters)			85 dB
Antenna Weight	8.1 lbs.	6.5 lbs.	9.3 lbs.	7 lbs.
Antenna Dimensions	16.1"L x 10.1"W x 3.4"H	16.1"L x 9.6"W x 2.1"H	16.8"L x 11.5"W x 2.8"H	16.1"L x 10"W x 2.8"H
Operating Temperature	-40°F to +140°F (-40°C to +60°C)			
Storage Temperature	-40°F to +158°F (-40°C to +70°C)			
Environmental Compatibility	MIL-STD-810			

* Larger BUC sizes available

ThinKom

www.thinkom.com

4881 West 145th Street, Hawthorne, CA 90250 USA 1.310.371.5486

© 2022 ThinKom Solutions, Inc. All rights reserved. ThinKom Solutions reserves the right to make changes in its products or specifications at any time and without notice. All trademarks indicated as such herein are trademarks of ThinKom Solutions.

© Reg. U.S. Patent and Trademark Office.

ThinPack Rev 03/22