

The Benchmark for Performance



ThinAir Ku3030

With industry-leading performance and reliability, the ThinAir Ku3030 consistently delivers a premium passenger experience for global inflight broadband.

Key Features

- Pole-to-pole coverage, including at high and low latitudes
- Long-term reliability with patented design and minimal active components
- Ultra-low profile, reducing drag and associated fuel costs
- Gate-to-gate operation with low prime power demands
- High throughput: Up to 400 Mbps down and 100 Mbps up
- High spectral efficiency (up to 3 bits/Hz)

TECHNICAL SPECIFICATIONS



Compatibility

Operating Band: Ku-band

- Tx: 13.75 to 14.50 GHz
- Rx: 10.70 to 12.75 GHz

Constellations: GEO

Satellite Services: Agnostic; inquire for specific network certifications

Tracking and Agility

Azimuth Coverage: 360° continuous

Elevation Coverage: +7.5° to +90° (network dependent)

Beam Agility: >200°/sec

Tracking Accuracy: <0.2°

Throughput and Performance

(Typical, at mid-band, cruise conditions, not including radome)

Data Rates: Up to 400 Mbps down and 100 Mbps up (network dependent)

G/T: 18.5 dB/K peak (14 dB/K at 20° elev.)

Network Efficiency: Up to 3 bits/Hz

EIRP (Psat): 57 dBW at broadside (52.5 dBW at 20° elev., 100 W Psat SSPB);

assumes 1.5 dB SSPA-to-Tx LRU interconnect losses

Transmit EIRP Spectral Density: (per 47 CFR 25.227)

- 41 to 44 dBW/4 MHz ESD at high latitudes (to 75° N/S)
- 39 to 42 dBW/4 MHz ESD at low to mid latitudes (to 50° N/S)

Geo-Plane Beamwidth: 1.8° Tx and 2.1° Rx

Geo-Plane Patterns: First sidelobe -22 dB typical

Polarization: Tracking linear (co/orthogonal), simultaneous dual-pol mode

Cross-Pol Isolation: 30 dB typical

Environmental

Operating Temperature: -55°C to +74°C external

Environmental Compatibility: RTCA/DO-160G

	Size	Weight	Avg Power
Tx Antenna	35.7 X 35.7 X 4.2 in	81 lb	23 W
Rx Antenna	35.7 X 35.7 X 4.2 in	83 lb	33 W
KRFU	18 X 9 X 3 in	15 lb	400 W
KANDU	18 X 9 X 5.5 in	17 lb	55 W

Other Applications

The Ku3030's design and performance characteristics are also well suited for special-mission aircraft.

ThinKom

www.thinkom.com

4881 West 145th Street, Hawthorne, CA 90250 USA

1.310.371.5486

© 2023 ThinKom Solutions, Inc. All rights reserved. ThinKom Solutions reserves the right to make changes in its products or specifications at any time and without notice. All trademarks indicated as such herein are trademarks of ThinKom Solutions.

© Reg. U.S. Patent and Trademark Office.

TAKu3030Rev 05/23